

# ACCU-LABS INC.

4831 S. Whipple Avenue  
Chicago IL 60632  
Phone: 773.523.3100 Fax: 773.523.4008  
[www.accu-labs.com](http://www.accu-labs.com)

**A2LA Accredited ISO/IEC 17025:2005 Certificate # 2558.01**

## PATSTRIP NI-E

**Patstrip NI-E is an electrolytic, non-cyanide stripper for removing nickel and other metals from steel.**

**Patstrip NI-E was developed to eliminate the use of cyanide and short-lived compounds for stripping nickel from steel. It can also be used for stripping copper, chrome, zinc, cadmium and electroless nickel.**

**Patstrip NI-E is used with REVERSE CURRENT and when properly operated has a long bath life with minimal fuming.**

### OPERATING GUIDELINES:

<b>Concentration</b>	3-4 LBS/Gallon of Patstrip NI-E per gallon of water.
<b>Operating pH</b>	Optimum range is 5.5-7.5, when pH exceeds 8.0 it can be lowered by making small additions of dilute nitric acid to the bath.
<b>Temperature</b>	Room temperature is recommended. DO NOT OPERATE PATSTRIP NI-E ABOVE 100°F AS IT COULD PIT THE STEEL!
<b>Current Density</b>	6-9 volts, 100 amps per square foot minimum.
<b>Dwell Time</b>	Dependant upon thickness of material to be stripped.
<b>Equipment</b>	Tanks should be steel with steel cathodes. Racks should be mild steel or titanium. DO NOT USE STAINLESS STEEL OR COPPER ALLOYS!
<b>Additional Maintenance</b>	As sludge eventually accumulates in the bottom of the tank it is recommended to occasionally siphon off supernatant liquid in the tank, removing and disposing of settled sludge from the bottom of the tank and dispose of properly. Refill tank with supernatant liquid and add corresponding amount of fresh water and fresh PATSTRIP NI-E and resume stripping operation.

**SAFETY:**

**Proper personal protective equipment including eye protection should be worn when working with or around this product. Read MSDS prior to use.**

**DISCLAIMER:**

*The information contained in this technical bulletin is true and accurate to the best of our knowledge. Because use and conditions are beyond our control, no guarantee is expressed or implied for the above suggestions or recommendations. Accu-Labs, Inc. will not incur any liability in connection with the use of these suggestions or technical data.*