

# ACCU-LABS INC.

4831 S. Whipple Avenue  
Chicago IL 60632  
Phone: 773.523.3100 Fax: 773.523.4008  
[www.accu-labs.com](http://www.accu-labs.com)

**A2LA Accredited ISO/IEC 17025:2005 Certificate # 2558.01**

## **UL - 1**

### **CONCENTRATED DEFOAMER FOR AQUEOUS SYSTEMS**

**UL - DEFOAMER is formulated to eliminate the problem of excessive foaming in cleaning processes and wastewater treatment. UL - 1 DEFOAMER is an easy to use liquid emulsion and it is completely free of any silicones.**

#### **ADVANTAGES**

<b>Highly concentrated:</b>	<b>Very cost effective</b>
<b>Versatile product:</b>	<b>Can be used in many applications</b>
<b>Non-silicone formula:</b>	<b>Will not contaminate production baths</b>

#### **GUIDELINES FOR USE:**

**There is not specific schedule by which UL - 1 DEFOAMER is used. This product should be added only on an as needed basis to control undesirable foaming in cleaners, etchants, and pollution control systems. In general:**

- 1. This product is an emulsion and MUST BE MIXED prior to use.**
- 2. It is to be used sparingly. In effluent streams, 0.5 liters per 5000 gallons is typical.**
- 3. Proper rinsing is important when UL - 1 DEFOAMER is used prior to plating. Contamination of plating solutions may affect brightener systems.**
- 4. Do not add UL - DEFOAMER directly into plating solutions.**

#### **SAFETY AND HANDLING**

**UL - 1 DEFOAMER may cause skin and eye irritation. Use only with suitable protective gear. Wash thoroughly after using. Refer to Material Safety Data Sheet for more complete information.**

**NOTICE OF DISCLAIMER: *The information contained in this bulletin is, to the best of our knowledge, true and accurate. All recommendations are made without guarantee. Accu-Labs, Inc. disclaims any and all liability arising from the use of this product or the information contained herein.***