

ACCU-LABS INC.

4831 S. Whipple Avenue
Chicago IL 60632
Phone: 773.523.3100 Fax: 773.523.4008
www.accu-labs.com

A2LA Accredited ISO/IEC 17025:2005 Certificate # 2558.01

710 ECO-TREAT

For treatment & removal of complexed cyanides in wastewater

ADVANTAGES

- Easy to use
- Single component
- Stable
- Works well over wide pH range
- Precipitates complexed cyanides

FOR REMOVAL OF COMPLEXED CYANIDES

1. Adjust pH of treatment effluent to 1.0 – 6.0.
2. Add the required amount of 710 Eco-Treat with agitation. One liter will precipitate approximately 25 ppm of total cyanide in 100 gallons of effluent.
3. Adjust pH to 7.5 – 9.0 for precipitation of Zinc Ferro cyanide, as well as any other metallics amenable to precipitation at that pH.

710 Eco-Treat may also be used for chrome reduction and separation, as well as precipitation of Ferricyanides from aluminum chromate rinse effluents.

HANDLING: Proper personal protective gear including eye protection should be worn when working with or around this product; read MSDS prior to use.

DISCLAIMER: *The information contained in this bulletin is, to the best of our knowledge, true and accurate. All recommendations are made without guarantee. Accu-Labs, Inc. disclaims any and all liability arising from the use of this product or information contained herein.*